


TARAFLEX® TABLE TENNIS 4.5

Description	Standard	Requirement	Unit	TARAFLEX® TT 4.5
Product Description				
Total thickness	EN 428	-	mm	4.5
Weight	EN 430	-	kg/m ²	2.6
Width of sheet	EN 426	-	lm	1.5
Length of sheet	EN 426	-	lm	20.5 STD
Sport Characteristics				
Vertical deformation	EN 14809	≤3.5	mm	≤3.5
Energy return	NF P 90 203	≥0.31	m/s	≥0.31
Sliding coefficient	EN 13036-4	80 - 110	-	80 - 110
Ball bounce	EN 12235	≥90	%	≥90
Technical Characteristics				
Abrasion resistance	EN ISO 5470-1	≤1000	mg	≤350
Impact resistance	EN 1517	≥8	N/m	≥8
Indentation resistance	EN 1516	≤0.5	mm	≤0.5
Surface treatment	-	-	-	PUR Protect
Surface complex	-	-	-	100% PVC
Foam backing	-	-	-	-
Anti-bacterial and fungicidal treatment	-	-	-	Sanosol
Anti-bacterial activity (E. coli - S. aureus - MRSA)	ISO 22196			Anti-bacterial > 99.9 %
Classification				
TVOC after 28 days	ISO 16000 - 6	µg/m ³		<100
CE Marking				
		EN 14904:2006	<div style="border: 1px solid black; border-radius: 10px; padding: 2px; display: inline-block;">EN ISO 5470-1</div> <div style="border: 1px solid black; border-radius: 10px; padding: 2px; display: inline-block; margin-left: 20px;">EN 13 501-1</div> <div style="border: 1px solid black; border-radius: 10px; padding: 2px; display: inline-block; margin-left: 20px;">EN 13 036- 4</div>	