

# TARASAFE ULTRA



COMFORT


COMFORT

Heavy traffic

SLIP RESISTANT

SLIP RESISTANT

## High performance vinyl safety flooring for contract applications



**8701 Opal**  
LRV: 59.1 - WR: 0603



### Performances and benefits



Brighter, cleaner crystal particles that add real sparkle



High resistance to heavy traffic




Matt finish for an improved design experience




Easier to cut-up 5 times more blade life




Easier to install, lighter & more flexible to handle




**7482 Halite**  
LRV: 32.5 - WR: 0500




**8704 Pebble**  
LRV: 44.1 - WR: 0173



**7383 Diopside**  
LRV: 59.6 - WR: 2416




**4323 Sandstone**  
LRV: 51.5 - WR: 2350




**4463 Aqua**  
LRV: 35.1 - WR: 2668




**8709 Granite**  
LRV: 25.4 - WR: 0033



**7384 Citrine**  
LRV: 40.2 - WR: 2174




**4505 Peridot**  
LRV: 35.5 - WR: 2499




**4465 Cobalt**  
LRV: 23.6 - WR: 0190




**8710 Basalt**  
LRV: 11.9 - WR: 2530




**8013 Jasper**  
LRV: 23.5 - WR: 2282




**4508 Jade**  
LRV: 26.1 - WR: 2418




**4472 Moonstone**  
LRV: 12.6 - WR: 0905




**8717 Obsidian**  
LRV: 10.1 - WR: 2238



**4128 Ruby**  
LRV: 13.8 - WR: 2947



**4460 Topaz**  
LRV: 23 - WR: 2434



**4470 Sapphire**  
LRV: 17.1 - WR: 2165



Comfort sheet with foam backing - Compact sheet without foam backing

Colour reference available as **TARASAFE ULTRA H20**

Ask for the **Tarasafe Ultra H20** sample card!

LRV: Light Reflectance Value

WR: Welding Rod = 0585 + colour code number

\* For more details visit the [greenguide.org.uk](http://greenguide.org.uk)

**IN YOUR LOCAL  
DISTRIBUTOR NOW!**

**Gerflor**  
theflooringroup

# SAFETY FLOORING

gerflor.com


**TARASAFE ULTRA & ULTRA COMFORT** are slip resistant safety vinyl floorcoverings, with a PVC wear layer and deeply **inlaid mineral crystal particles** (patented) and coloured chips for a decorative design. They are reinforced with a glass fibre grid and are available in a sheet format. The ranges are ideal for **heavy traffic applications** where slip resistance, durability, hygiene and easy maintenance are required. Suitable for most contract & commercial areas, they are a popular choice in the education and healthcare environments, the matt finish surface is also perfectly suitable for dementia care units. They are eco-friendly, 100% recyclable, Floorscore® certified and do not contain any heavy metals or CMR 1&2. They are also 100% compliant with REACH.

The product emission rate of volatile organic compounds is < 100 µg/m<sup>3</sup> (TVOC after 28 days – ISO 16000 -6).

The **SparClean®** surface treatment improves the product performance in terms of stain and dirt resistance and designs last longer for extended durability. **TARASAFE ULTRA COMFORT** has a VHD closed cell foam backing yielding a 16dB sound insulation.

			Tarasafe Ultra	Tarasafe Ultra Comfort
<b>DESCRIPTION</b>				
Total Thickness	EN ISO 24346 (EN 428)	mm	2.0	3.2
Thickness of wearlayer	EN ISO 24340 (EN 429)	mm	0.85	0.85
Weight	EN ISO 23997 (EN 430)	g/sq.m	2460	2960
Width/Length of Sheet	EN ISO 24341 (EN 426)	cm/lm	200/20	200/20
<b>CLASSIFICATION</b>				
Norm/Product Specification	-	-	EN ISO 10582 (EN 649)	EN 651
European classification	EN ISO 10874 (EN 685)	class	34-43	34-42
Fire Rating	EN 13501-1	class	Bfl-s1	Bfl-s1
Static electrical propensity	EN 1815	kV	< 2	< 2
Slip resistance: Pendulum Test (dry & wet)	BS 7976-2	PTV	> 36	-
Surface roughness Rz	-	µm	≥ 20	-
Slip resistance wet: ramp test with oil	DIN 51 130	class	R10	R10
Slip resistance wet: ramp test with water	DIN 51 097	class	B	-
Slip resistance – ramp test	EN 13845 (annex C)	class	ESf-ESb	-
<b>PERFORMANCE</b>				
Wear Resistance	EN 660.2	mm <sup>3</sup>	≤ 2	≤ 2
Wear group	NF 189	group	T	T
Type binder content	EN ISO 10582	type	I	-
Dimensional stability	EN ISO 23999 (EN 434)	%	≤ 0.40	≤ 0.40
Residual indentation	EN ISO 24343-1 (EN 433)	mm	≤ 0.03	≤ 0.20
Impact sound insulation	EN ISO 717-2	dB	-	16
Castor Chair test (type W)	ISO 4918 (EN 425)	-	OK	OK
Thermal Conductivity	EN ISO 10456 (EN 12524)	W/(m.K)	0.25	0.25
Colour Fastness	EN 20 105-B02	degree	≥ 6	≥ 6
Surface Treatment	-	-	SparClean®	SparClean®
Chemical Products Resistance	EN ISO 26987 (EN 423)	-	OK	OK
Anti-bacterial activity (MRSA) <sup>(1)</sup>	ISO 22196	-	> 99% Inhibits growth	> 99% Inhibits growth
<b>ENVIRONMENT / INDOOR AIR QUALITY</b>				
TVOC after 28 days	ISO 16000-6	µg/m <sup>3</sup>	< 100	
Certification	-	-	Floorscore®	
<b>CE MARKING</b>				
CE	EN 14 041	-		

(1) The implementation of an effective cleaning method is the best defence against infection.



UK reference

Installation and Maintenance Guidelines, Complementary ranges available on our Gerflor website.

**IMPORTANT:** The information contained in this document is valid from 1/01/2018 and is subject to change at any time without notice. In the context of constantly changing technology, our customers are responsible, prior to any use, for checking with us that this document is the version in force.



Rubber leaves indelible stains on vinyl floorings: do not use mats with rubber backing and replace tubular furniture feet with those made of PVC or polyamide. Place mats of sufficient length at entrances to reduce outside sources of dirt.

## TARASAFE ULTRA, LESS SPEAKING FOR MORE ACTIONS



**COMPOSITION**  
100% REACH



**INDOOR AIR QUALITY**  
10 times lower than norms requirements  
(TVOC < 100ug/m<sup>3</sup> after 28 days)



**RECYCLABILITY**  
100%



**LCA**  
Eco-designed according to a product specific life cycle analysis



**WELLNESS**  
Anti slip R10